

Vapor Pro[®] XL

Moisture specific analyzer

Quick and accurate moisture analysis for a wide range of applications.



Specifications

Moisture Range	- 10 ppm (10 µg 0.001%) to 100%	Operating Environment	- 32-40°C at <50% RH; 0-31°C at <80% RH
Moisture Resolution	- 1 ppm (0.1 µg 0.0001%)	Power Requirements	- 100-120 VAC, 50/60 Hz, 8A or 220-240 VAC, 50/60 Hz, 4A
Repeatability	- <10% C.V. for samples >0.1% moisture <15% C.V. for samples <0.1% moisture	Dimensions	- 6.8" H x 18.5" W x 11" D (17.2 cm W x 47 cm H x 27.9 cm D)
Temperature Range	- 25°C to 300°C	Weight	- 17.7 lbs. (8.0 kg)
Sample Size	- 0.01 g to 8 g	Warranty	- Two years, factory parts and labor (one year international)
Results	- % moisture, ppm moisture, µg water	Rear Panel Connections	- USB A and B, ethernet, serial port, carrier gas input and output
Memory	- Stores up to 250 test programs, last 1000 results and last 100 graphs	Carrier Gas	- Dry nitrogen or dry air (-40°C dew point or lower is suggested) at 17-22 psi (user supplied)
Statistical Analysis	- Mean, SD, CV	Touchscreen	- LCD 800 x 480 Color TFT
Ending Criteria	- User adjustable: Prediction, Rate, Time, Time then Rate	Certifications	- UL, CE
Calibration	- Manual calibration with NIST traceable capillary tubes		

The next generation in moisture analysis

Improved accuracy, precision, flexibility and an advanced user interface - the Vapor Pro[®] XL is the latest in moisture specific analysis technology from Computrac[®]. The Vapor Pro[®] XL is ideal for nearly any application in which Karl Fischer titration is used. It features an upgraded heater and increased control over testing temperatures.

The Vapor Pro[®] XL is completely chemical free and is compatible with multiple sizes of sample vials. It is also equipped with stepped temperature testing capabilities for enhanced method development.

Features



ZERO CHEMICAL REAGENTS:

The Vapor Pro® XL offers moisture specific analysis that correlates well with Karl Fischer without the hassle or expense of hazardous chemical reagents, costly glassware or time consuming maintenance.



VERSATILE:

From plastics and petroleum products to pharmaceuticals, chemicals and more, the Vapor Pro® XL is ideal for nearly any application in which Karl Fischer titration is used.



WEB SERVER:

The optional web server allows users to monitor tests remotely and check in with operators. It also lets users download results and calibration reports, view the audit log and transfer programs between instruments.



FLEXIBLE ENDING CRITERIA:

User adjustable ending criteria help to optimize test results and performance for your unique application.



TOUCHSCREEN:

The new color LCD touchscreen and intuitive interface require minimal training or existing knowledge base to operate. Everything is menu driven so that you'll get accurate, repeatable results regardless of who runs the test.



MULTIPLE SAMPLE VIAL SIZES:

Compatible with most crimp top vials from 2R to 60R, the Vapor Pro® XL allows users to test hygroscopic samples without removing them from their sample vials.



HIGH TEMPERATURE TESTING:

The upgraded heater increases the maximum testing temperature to 300°C and allows for improved control over testing temperatures across the range of the instrument.



DATA STORAGE:

The Vapor Pro® XL stores up to 250 test programs and retains the last 1000 test results and last 100 test graphs, enabling users to view and select past test results for statistical analysis and test a variety of samples with ease.



STEPPED TEMPERATURE TESTING:

The Vapor Pro® XL offers stepped temperature testing capabilities that make method development easier than ever before.

Methods & regulatory compliance

- **21 CFR PART 11 COMPLIANT (OPTIONAL):**
Meet regulatory compliance standards for pharmaceutical and medical device companies
- **ASTM D7191-18:**
Standard test method for determination of moisture in plastics by relative humidity sensor
- **ASTM D7546-15:**
Standard test method for determination of moisture in new and in-service lubricating oils and additives by relative humidity sensor